

MACtab White MP 747 Century 6

FACE MATERIAL

White w... free... or... c... wri... g... e...
 ab... e... te... with... air... ul... x... lett... or... s... gra... re... d... offset and
 n... la... s... ab... o... appl... ion... wh... tte... qu... y... n... ting... i... non-coated
 ish... is... qu... ir... .

DISCONTINUED

... application
 ... use... self-adhesive paper for a wide range of plain and
 ... applications, such as systems labels, on pack promotions and point of
 sale labels...

Technical Characteristics

Thickness	74 ± 5 µm	ISO 534
Weight	75 ± 5 gr/sqm	ISO 536
Tensile strength	min. 68 N/15 mm M.D. min. 40 N/15 mm C.D.	ISO 1924-1
Opacity	≥ 84 %	ISO 2471
Smoothness	min 180 sec	Bekk

ADHESIVE

Permanent rubber based adhesive combining all purpose properties with a good initial tack. It is suitable for use on a wide variety of substrates (except where there is presence of plasticizers) and enables optimum converting speeds for regular shapes of labels.

Certification : Indirect contact foodstuffs (21557 U 05)

Properties

Quick Tack	≥ 11	N/25 mm on stainless steel	FTM 9
Application temperature	above + 5°C		
Service temperature	- 20°C to + 70°C		

BACKING

Super calendered glassine backing paper combining high flexibility and consistent caliper for speed and ease of conversion with good translucency for optical scanning. Excellent resistance to die cutting.

Technical Characteristics

Thickness	55 ± 6 µm	ISO 534
Weight	60 ± 5 gr/m ²	ISO 536
Tensile strength	min. 5 kN/m	M.D. ISO 1924
Transparency	minimum 46 %	DIN 53147

Shelf life: 2 years when stored at 15-25°C, 50 % relative humidity, in the original packaging.



MACtac Europe
Bd Kennedy, Zoning Industriel, Zone B
B-7060 Soignies Belgium
Phone : +32 (0) 67 346 211
Fax : +32 (0) 67 346 339
www.mactac-europe.com
e-mail : mactac.europe@mactac.com

All MACtac products are subject to careful quality control throughout the manufacturing process and are warranted to be of quality and free from manufacturing defects.

Published information concerning MACtac products is based upon research which the Company believes to be reliable although such information does not constitute a warranty.

Because of the variety of uses of MACtac products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.