

GLOSSOPAQUE MP 505 - 0

Century 6

FACE MATERIAL

White wood free coated paper with a fine grain finish. Glossopaque is produced by a computer process such as excimerpress, offset, and digital printing.

Application

Glossopaque is ideally used when total opacity is required: for masking old prices, printing new information or for texts to be over-printed or to be replaced by new information.

Technical Characteristics

Thickness	70 ± 7 µm	ISO 534
Weight	33 ± 5 gr/sqm	ISO 536
Tensile strength	min. 6 N/15 mm S.M.	ISO 1924-1
Transparency	min. 30 %	C.D.
Shelf life	min. 24 %	DIN 6750

ADHESIVE

Rubber based permanent opaque adhesive presenting excellent adhesion and tack properties.

Adhesive MP 505 is suitable for use on a wide variety of surfaces including non-polar substrates such as polyethylene and polypropylene (not recommended for use on plastic substrates, like soft PVC) and offers a good resistance to low temperatures.

Properties

Quick Tack	min. 10	N/25 mm on stainless steel	FTM 9
Release force	0,66 ± 0,2	N/25 mm at 80 m/min	FTM 4
Application temperature	min. -5°C		
Service temperature	-30°C to +60°C		

BACKING

Super calendered glassine backing paper combining high flexibility and consistent caliper for speed and ease of conversion with good translucency for optical scanning. Excellent resistance to die cutting.

Technical Characteristics

Thickness	55 ± 6 µm	ISO 534
Weight	60 ± 5 gr/m ²	ISO 536
Tensile strength	≥ 5 kN/m S.M.	ISO 1924
Transparency	minimum 46 %	DIN 53147

Shelf life: 2 years when stored at 15-25°C, 50 % relative humidity, in the original packaging.



MACtac Europe
Bd Kennedy, Zoning Industriel, Zone B
B-7060 Soignies Belgium
Phone : +32 (0) 67 346 211
Fax : +32 (0) 67 346 339
www.mactac-europe.com
e-mail : mactac.europe@mactac.com

All MACtac products are subject to careful quality control throughout the manufacturing process and are warranted to be of quality and free from manufacturing defects.

Published information concerning MACtac products is based upon research which the Company believes to be reliable although such information does not constitute a warranty.

Because of the variety of uses of MACtac products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.