


# Complex Supergloss MP 196 Century 6

**FIGURE**



**FACE MATERIAL**

This complex construction is made up of a front material and a glassine liner that is itself coated with adhesive on the other side and protected by a second glassine liner giving a product with 2 permanent adhesives.

This self adhesive complex is used where a face material can be easily removed from its liner in order to be placed on another substrate. This kind of material is designed for promotional campaign subscription, follow up labels for express mail, register keeping of sales or stocks, discount coupon, etc. For applications on very curved surfaces (< 15mm diameter), we recommend our Macflex face stock.

Supergloss

**White wood free cast coated paper with mirror finish.**

Supergloss is printable by all common printing processes with excellent results on flexo, letterpress and gravure and hot foil stamping.

**Technical Characteristics**

<b>Thickness</b>	80 ± 8 µm	ISO 534
<b>Weight</b>	80 ± 5 gr/m <sup>2</sup>	ISO 536

**ADHESIVE**

**Permanent acrylic adhesive emulsion based** offering a perfect combination of quick tack and shear resistance and an outstanding adhesion to most substrates. MP 196 is a multipurpose adhesive suitable for high converting speeds achieving optimal dispensing. MP 196 complies with the BgVV regulation for direct contact with some foods (details available on request.)

**Certification** : Direct contact dry and moist non-fatty foodstuffs (21420 U 05)

**Properties**

<b>Quick Tack</b>	≥ 13	N/25 mm on glass	FTM 9
<b>Application temperature</b>	min. + 5 °C		
<b>Service temperature</b>	- 15 °C to + 90 °C		

## BACKING

Super calendered glassine backing paper combining high flexibility and consistent caliper for speed and ease of conversion with good translucency for optical scanning. Excellent resistance to die cutting.

Technical Characteristics		
Thickness	55 ± 6 µm	ISO 534
Weight	60 ± 5 gr/m <sup>2</sup>	ISO 536
Tensile strength	Minimum 75N/15mm M.D	ISO 1924
Transparency	minimum 46 %	DIN 53147

**Shelf life:** 2 years when stored at 15-25°C, (50 ± 5) % relative humidity, in the original packaging.



MACtac Europe  
Bd Kennedy, Zoning Industriel, Zone B  
B-7060 Soignies Belgium  
Phone : +32 (0) 67 346 211  
Fax : +32 (0) 67 346 339  
[www.mactac-europe.com](http://www.mactac-europe.com)  
e-mail : mactac.europe@mactac.com

*All MACtac products are subject to careful quality control throughout the manufacturing process and are warranted to be of quality and free from manufacturing defects.*

*Published information concerning MACtac products is based upon research which the Company believes to be reliable although such information does not constitute a warranty.*

*Because of the variety of uses of MACtac products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.*