



MACal 8129 n.t.c. MP 450 Century 8 White

FACE MATERIAL

Soft cadmium free, white gloss vinyl, calendered, monomeric plasticized.

The material can be printed in screen, flexo, letterpress and gravure and can also be used for hot foil stamping with suitable ribbon quality.

Application

Long life labels and outdoor use. Labels, stickers, signs, emblems, vehicle marking, drum labelling and other applications where conformability, longer life and resistance to weather and chemical agents are required.

Technical characteristics

Thickness	90 ± 7 µm	ISO 534
Weight	123 ± 12 gr/m ²	ISO 536
Tensile strength CD	≥ 32 N/15mm	DIN 53455
Resistance MD	≥ 30 N/15mm	DIN 53455
Gloss (20°)	± 45 %	DIN 67530

ADHESIVE

A rubber based permanent adhesive with good tack and adhesion to a wide variety of surfaces (is not recommended for substrates containing migrating plasticizers).UV resistance is considered as good if not exposed to direct sunlight.

Properties

High Speed Release	0,35 ± 0,08	N/25mm at 100 m/min.	FTM 4
Low Speed Release	0,08 ± 0,04	N/25mm at 300 mm/min.	FTM 3
Quick Tack	≥ 11	N/25 mm on glass	FTM 9
Peel 20 min	≥ 13	N/25 mm on glass	FTM 1
Cohesion	≥ 60	Hours on glass	FTM 8
Appl. temperature	≥ + 5°C		
Service temperature	from -20 to +80°C		
Shrinkage	≤ 3 %	80°C – 10 min	

BACKING

Super calendered glassine backing paper combining high flexibility and consistent calliper for speed and ease of conversion with good translucency for optical scanning. Excellent resistance to die-cutting.

Technical characteristics

Thickness	68 ± 6 µm	ISO 534
Weight	80 ± 4 gr/m ²	ISO 536
Tensile strength MD	≥ 90 N/15 mm	DIN 53455
Resistance CD	≥ 50 N/15 mm	DIN 53455
Transparency	≥ 42 %	DIN 53147

Shelf life : 2 years when stored at 15-25°C, (50 ± 5) % relative humidity, in the original packaging.



MACTac Europe
Bd Kennedy, Zoning Industriel, Zone B
B-7060 Soignies Belgium
Phone : +3267/346 211
Fax : +3267/346 339
www.mactac-europe.com
e-mail : mactac.europe@mactac.com

All MACTac products are subject to careful quality control throughout the manufacturing process and are warranted to be of quality and free from manufacturing defects.

Published information concerning MACTac products is based upon research which the Company believes to be reliable although such information does not constitute a warranty.

Because of the variety of uses of MACTac products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.