

## MACtab White MP 125 S Secury 9

### FACE MATERIAL

**White wood-free, non-coated writing paper.**

MACtab may be printed with fair results by flexo, letterpress, gravure and offset and particularly suitable for applications where better quality printing with a non-coated finish is required.

#### Application

It is suitable as universal use self-adhesive paper for a wide range of plain and multicolour label applications, such as systems labels, on pack promotions and point of sales labels...

#### Technical Characteristics

<b>Thickness</b>	71 ± 5 µm	ISO 534
<b>Weight</b>	73 ± 7 gr/sqm	ISO 536
<b>Tensile strength</b>	min. 82 N/15 mm M.D. min. 37 N/15 mm C.D.	ISO 1924-1
<b>Opacity</b>	≥ 82 %	ISO 2471
<b>Bekk level</b>	min 300 sec	Bekk

### ADHESIVE

**Permanent acrylic adhesive, emulsion based,** offering a perfect combination of quick tack and shear resistance, and outstanding adhesion to most substrates. This adhesive is a multi-purpose ones suitable for high converting speeds.

**Certification :** Direct contact dry and moist non-fatty foodstuffs ( 25268 U 07 )

#### Properties

<b>Quick Tack</b>	min. 10	N/25 mm on glass	FTM 9
<b>Low release force</b>	0,07 ± 0,02	N/25 mm at 300 mm/min.	FTM 3
<b>Application temperature</b>	above + 5°C		
<b>Service temperature</b>	- 15°C to + 80°C		

### BACKING

Special quality white one side coated siliconed kraft backing paper.

Excellent mechanical properties such as dimensional stability.

Very good characteristics for fan folding applications.

#### Technical Characteristics

<b>Thickness</b>	90 ± 7 µ	ISO 534
<b>Weight</b>	80 ± 6 gr/sqm	ISO 536
<b>Opacity</b>	minimum 85 %	ISO 2471

**Shelf life:** 2 years when stored at 15-25°C, (50 ± 5) % relative humidity, in the original packaging.



MACtac Europe  
Bd Kennedy, Zoning Industriel, Zone B  
B-7060 Soignies Belgium  
Phone : +32 (0) 67 346 211  
Fax : +32 (0) 67 346 339  
[www.mactac-europe.com](http://www.mactac-europe.com)  
e-mail : [mactac.europe@mactac.com](mailto:mactac.europe@mactac.com)



*All MACtac products are subject to careful quality control throughout the manufacturing process and are warranted to be of quality and free from manufacturing defects.*

*Published information concerning MACtac products is based upon research which the Company believes to be reliable although such information does not constitute a warranty.*

*Because of the variety of uses of MACtac products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice.*